



DECLARATION OF PERFORMANCE – Gas Seal Black

1. Unique identification code of the product-type:


RIW Gas Seal Black

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

See item 1. (stated on packaging and printing of the product)

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Function: insulation against earth humidity.



4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

RIW Ltd, Arc House, Terrace Road South, Binfield, Berkshire, RG42 4PZ

Tel.: 01344 397777

www.riw.co.uk

5. Name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Not listed

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

2+

7. Declaration of performance concerning a construction product covered by a harmonised standard:

***EN 13967:2004+A1:2006, Notified body No. 0799 - KIWA MPA
Bautest Greven performed initial inspection of the
manufacturing plant and of factory production control and
continuous surveillance, assessment and evaluation of factory
production control under system 2+ and issued certificate of
conformity of the factory production control.***





- 8.** Declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Not issued

- 9.** Declared performance:

Essential characteristics		Performance			Harmonised technical specification
	Units	Nominal value	Tolerance		
Reaction to fire	degree	E	-	-	EN 13501-1 / 15s
Watertightness	[-]	conforming	-	-	EN 1928 method A
Maximal tensile force MD / CMD	[N/50mm]	>500 / >380	-	-	EN 12311-2 method A
Joint strength MD / CMD	[N/50mm]	npd npd	- weld - joint bitumen-rubber tape		EN 12317-2
Resistance to tearing MD / CMD	[N]	>320 / >320	-	-	EN 12310-1
Resistance to static loading	[kg]	>20	-	-	EN 12730
Determination of resistance to impact	[mm]	npd	-	-	EN 12691
Durability (artificial ageing):					
-Resistance at elevated temperature	[-]	conforming	-	-	EN 1296
-Resistance to liquid chemicals	[-]	conforming	-	-	EN 1847

Note: "npd" = no performance determined

- 10.** The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

This product does not contain any dangerous substances (according to REACH No. 1907/2006).

Signed for and on behalf of the manufacturer by

Ing. Jiří Hlavatý
Chairman of the board

In Dvůr Králové nad Labem, 12.05.2014



RIW Limited, Arc House, Terrace Road South, Binfield, Berkshire, RG42 4PZ

T: 01344 397 777 E: enquiries@riw.co.uk

www.riw.co.uk