

RIW GENERAL ANCILLARIES

RIW Adhesive Tape

Used to temporarily adhere following items to RIW membranes or to link polyethylene type sheet DPMs to certain RIW products.

RIW Aggregates (Grades 1 & 2)

Used with RIW Toughseal to provide a slip retardant surface or key for following wet trade finishes.

RIW Cleaning Solvent

Used for cleaning brushes etc, or to re-activate resin-based coatings.

RIW Flexitape

Used with RIW Repel AC to reinforce joints etc.

RIW GM Reinforcing Scrim

Used with RIW Liquid GM to reinforce joints etc.

RIW Jointing Tape

Used with RIW Sheetseal 9000 DPC, to join rolls together, and/or to lap the product onto other items.

RIW Protection Board

Used to protect applied membranes etc, from following works.

RIW Toughseal Reinforcing Tape

Used over RIW Toughseal to reinforce joints etc, when a 'key' for following wet trade finishes is required.

RIW Universal Tape

Used beneath Flexiseal to separate and bridge over joints.

GENERAL ANCILLARIES

ADHESIVE TAPE

Adhesive Tape is a double-sided bitumen/rubber self-adhesive tape with a removable silicone release paper one side and a thin polyethylene removable sheet on the other.

APPLICATION

Designed to be used in conjunction with Protection Board or Double Drain, to temporarily adhere it to dry surfaces of membranes.

It is used in pads of 150mm square, or in strips of a suitable length. It can also be used to adhere other materials, such as polyethylene sheets or similar, to most 'dried' RIW membranes.

The product can be easily cut with a craft knife.

PACKAGING

Adhesive Tape	150mm wide rolls x15m long Weight = 4kg/roll
---------------	---

AGGREGATE GRADE 1

Crushed flint

Sieve size:	2.000mm = 99 - 100%
	1.180mm = 22 - 42%
	0.850mm = 00 - 6%

APPLICATION

Dressed into Toughseal to provide a key for following wet trade finishes.

PACKAGING

Aggregate Grade 1	25kg bags
-------------------	-----------

AGGREGATE GRADE 2

Crushed flint

Sieve size:	0.500mm = 98 - 100%
	0.425mm = 28 - 52%
	0.355mm = 8 - 19%
	0.300mm = 0 - 4%

APPLICATION

Dressed into Toughseal to provide a slip retardant finish.

PACKAGING

Aggregate Grade 2	25kg bags
-------------------	-----------

CLEANING SOLVENT

Aromatic hydrocarbon solvent ; Contains Xylene.

APPLICATION

Used for cleaning brushes, rollers, etc. Also used for cleaning and re-activating resin based coatings, such as Flexiseal and Toughseal.

This product must not be used as 'thinners'.

PACKAGING

Cleaning Solvent	5 litre tins
------------------	--------------

FLEXITAPE

Multi-directional nylon polyamide tape

APPLICATION

Use embedded in Repel AC, to reinforce joints etc, in the substrate. The product can be easily cut with a pair of scissors.

PACKAGING

Flexitape	75mm wide rolls x 50m long Weight = 280g/roll
-----------	--

GM REINFORCING SCRIM

GM Reinforcing Scrim is a 0.65mm thick, thermal bonded polyester fabric (non-woven).

APPLICATION

Use embedded in Liquid GM to reinforce corners, angles, joints/cracks etc, prior to application of the main Liquid GM coating application. The product can be easily cut with a pair of scissors or craft knife.

PACKAGING

GM Reinforcing Scrim	300mm wide rolls x 100m long Weight = 70g/m ²
----------------------	---

JOINTING TAPE

Jointing Tape is a double-sided butyl tape.

APPLICATION

Used with Sheetseal 9000 DPC to seal rolls of DPC together at laps. Also used to adhere rolls of DPC onto prefabricated items. The product can be easily cut with a pair of scissors or craft knife.

PACKAGING

Jointing Tape	100mm wide rolls x 15m long Weight = 3.06kg/roll
---------------	---

GENERAL ANCILLARIES

PROTECTION BOARD

Protection Board is a flat sheet, made of organic fibres saturated with bitumen. The board is resistant to water, ground salts and most corrosive chemicals.

APPLICATION

Use to protect waterproof membranes against mechanical damage, pedestrian or vehicular traffic and abrasion caused by backfilling.

The product can be easily cut with a craft knife.

PACKAGING

Protection Board	2020 x 900mm x 3mm thick Weight = 2.7 kg/m ²
------------------	--

TOUGHSEAL REINFORCING TAPE

Toughseal Reinforcing Tape is a bitumen/rubber self-adhesive tape with a removable silicone release paper on one side and a thin polyethylene removable sheet on the other.

APPLICATION

Use to reinforce corners, angles, joints etc, after application of Toughseal, when wet trade finishes are required.

The product can be easily cut with a craft knife.

PACKAGING

Toughseal Reinforcing Tape	150 wide rolls x 15m long Weight = 3kg/roll
----------------------------	--

UNIVERSAL TAPE

Universal Tape is a self-adhesive vinyl tape.

APPLICATION

Designed to be used where Flexiseal needs to be lapped onto Sheetseal 226.

Also used in conjunction with Flexiseal, when a slip tape is required at joints.

The product can be easily cut with a pair of scissors or craft knife.

PACKAGING

Universal Tape	48mm wide rolls x 50m long
----------------	----------------------------

The information in this literature was correct at the time of going to press. However, we are committed to continually improving our products and reserve the right to change product specifications.

For the latest information, please consult RIW. Conditions of use are beyond our control, therefore we cannot warrant the results to be obtained.

RIW

Arc House, Terrace Road South, Binfield,
Bracknell, Berkshire, RG42 4PZ

Technical enquires tel: **01344 397777**

Commercial enquires tel: **01344 397788**

www.riw.co.uk

REMEMBER IT'S
waterproof RIW