

# RIW GENERAL ANCILLARIES

## **RIW Adhesive Tape**

Used to temporarily adhere following items to RIW membranes or to link polyethylene type sheet DPMs to certain RIW products.

## **RIW Aggregates (Grades 1 & 2)**

Used with RIW Toughseal to provide a slip retardant surface or key for following wet trade finishes.

## **RIW Cleaning Solvent**

Used for cleaning brushes etc, or to re-activate resin-based coatings.

## **RIW Flexitape**

Used with RIW Repel AC to reinforce joints etc.

## **RIW GM Reinforcing Scrim**

Used with RIW Liquid GM to reinforce joints etc.

## **RIW Jointing Tape**

Used with RIW Sheetseal 9000 DPC, to join rolls together, and/or to lap the product onto other items.

## **RIW Protection Board**

Used to protect applied membranes etc, from following works.

## **RIW Toughseal Reinforcing Tape**

Used over RIW Toughseal to reinforce joints etc, when a 'key' for following wet trade finishes is required.

## **RIW Lap Tape**

Used beneath Flexiseal Pro for crack bridging.

# GENERAL ANCILLARIES

## ADHESIVE TAPE

Adhesive Tape is a double-sided bitumen/rubber self-adhesive tape with a removable silicone release paper one side and a thin polyethylene removable sheet on the other.

### APPLICATION

Designed to be used in conjunction with Protection Board or Double Drain, to temporarily adhere it to dry surfaces of membranes.

It is used in pads of 150mm square, or in strips of a suitable length. It can also be used to adhere other materials, such as polyethylene sheets or similar, to most 'dried' RIW membranes.

The product can be easily cut with a craft knife.

### PACKAGING

|               |   |
|---------------|---|
| Adhesive Tape | 150mm wide rolls x15m long<br>Weight = 4kg/roll |
|---------------|---|

## AGGREGATE GRADE 1

Crushed flint

|             |                     |
|-------------|---------------------|
| Sieve size: | 2.000mm = 99 – 100% |
|             | 1.180mm = 22 – 42%  |
|             | 0.850mm = 00 – 6%   |

### APPLICATION

Dressed into Toughseal to provide a key for following wet trade finishes.

### PACKAGING

|                   |           |
|-------------------|-----------|
| Aggregate Grade 1 | 25kg bags |
|-------------------|-----------|

## AGGREGATE GRADE 2

Crushed flint

|             |                     |
|-------------|---------------------|
| Sieve size: | 0.500mm = 98 – 100% |
|             | 0.425mm = 28 – 52%  |
|             | 0.355mm = 8 – 19%   |
|             | 0.300mm = 0 – 4%    |

### APPLICATION

Dressed into Toughseal to provide a slip retardant finish.

### PACKAGING

|                   |           |
|-------------------|-----------|
| Aggregate Grade 2 | 25kg bags |
|-------------------|-----------|

## CLEANING SOLVENT

Aromatic hydrocarbon solvent ; Contains Xylene.

### APPLICATION

Used for cleaning brushes, rollers, etc. Also used for cleaning and re-activating resin based coatings, such as Flexiseal Pro and Toughseal.

This product must not be used as 'thinners'.

### PACKAGING

|                  |              |
|------------------|--------------|
| Cleaning Solvent | 5 litre tins |
|------------------|--------------|

## FLEXITAPE

Multi-directional nylon polyamide tape

### APPLICATION

Use embedded in Repel AC, to reinforce joints etc, in the substrate. The product can be easily cut with a pair of scissors.

### PACKAGING

|           |  |
|-----------|--|
| Flexitape | 75mm wide rolls x 50m long<br>Weight = 280g/roll |
|-----------|--|

## GM REINFORCING SCRIM

GM Reinforcing Scrim is a 0.65mm thick, thermal bonded polyester fabric (non-woven).

### APPLICATION

Use embedded in Liquid GM to reinforce corners, angles, joints/cracks etc, prior to application of the main Liquid GM coating application. The product can be easily cut with a pair of scissors or craft knife.

### PACKAGING

|                      |   |
|----------------------|---|
| GM Reinforcing Scrim | 300mm wide rolls x 100m long<br>Weight = 70g/m <sup>2</sup> |
|----------------------|---|

## JOINTING TAPE

Jointing Tape is a double-sided butyl tape.

### APPLICATION

Used with Sheetseal 9000 DPC to seal rolls of DPC together at laps. Also used to adhere rolls of DPC onto prefabricated items. The product can be easily cut with a pair of scissors or craft knife.

### PACKAGING

|               |   |
|---------------|---|
| Jointing Tape | 100mm wide rolls x 15m long<br>Weight = 3.06kg/roll |
|---------------|---|

# GENERAL ANCILLARIES

## PROTECTION BOARD

Protection Board is a flat sheet, made of organic fibres saturated with bitumen. The board is resistant to water, ground salts and most corrosive chemicals.

### APPLICATION

Use to protect waterproof membranes against mechanical damage, pedestrian or vehicular traffic and abrasion caused by backfilling.

The product can be easily cut with a craft knife.

### PACKAGING

|                  |  |
|------------------|--|
| Protection Board | 2020 x 900mm x 3mm thick<br>Weight = 2.7 kg/m <sup>2</sup> |
|------------------|--|

## TOUGHSEAL REINFORCING TAPE

Toughseal Reinforcing Tape is a bitumen/rubber self-adhesive tape with a removable silicone release paper one side and a thin polyethylene removable sheet on the other.

### APPLICATION

Use to reinforce corners, angles, joints etc, after application of Toughseal, when wet trade finishes are required.

**Silicone sealants must not be allowed to come into direct contact with the tape.**

The product can be easily cut with a craft knife.

### PACKAGING

|                            |   |
|----------------------------|---|
| Toughseal Reinforcing Tape | 150 wide rolls x 7.5m long<br>Weight = 2kg/roll |
|----------------------------|---|

## LAP TAPE

Lap Tape is a single-sided self-adhesive PVC tape used as a slip tape with Flexiseal Pro. The tape is applied at construction joints/cracks, over Flexiseal Pro Primer, prior to application of Flexiseal Pro.

### APPLICATION

Ensure all surfaces to be bonded are dry and free from dust, grease and other contaminants. Apply Lap tape equally lapped across joint/crack and smooth down to ensure full contact. The surface should then be rolled with hard roller to ensure good adhesion.

The product can be easily cut with a pair of scissors or craft knife.

### PACKAGING

|          |                             |
|----------|-----------------------------|
| Lap Tape | 100mm wide rolls x 50m long |
|----------|-----------------------------|

The information in this literature was correct at the time of going to press. However, we are committed to continually improving our products and reserve the right to change product specifications.

For the latest information, please consult RIW. Conditions of use are beyond our control, therefore we cannot warrant the results to be obtained.

## RIW Limited

487-488 Ipswich Road, Slough, SL1 4EP

Technical enquires tel: **01753 944200**

Commercial enquires tel: **01753 944210**

[www.riw.co.uk](http://www.riw.co.uk)

REMEMBER IT'S  
**waterproof** RIW