

Safety data sheet
according to 1907/2006/EC, Article 31

Printing Date: 09.01.2020

Version Number: 1.0

Revision Date: 09.01.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier:**Trade name: ***RIW FLEXISEAL 500 POWDER INITIATOR*****1.2 Relevant identified uses of the substance or mixture, and uses advised against:**

Relevant identified uses of the substance or mixture: Waterproofing.

Identified uses advised against: No further relevant information available.

1.3 Details of the supplier of the safety data sheet:**Manufacturer/supplier:**RIW Limited
580-581 Ipswich Road,
Slough, Berkshire
SL1 4EQ

Tel: +44 (0)1753 944210

www.riw.co.ukFurther information obtainable from: enquiries@riw.co.uk**1.4 Emergency telephone number:**

For Chemical Emergency: (Spill, Leak, Fire, Exposure or Accident) - Call CHEMTREC (Day/Night) on:

Within USA & Canada : 800-424-9300,

Outside USA & Canada : +1 703-741-5970

National emergency telephone number: CHEMTREC UK +(44)-870-8200418

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture:****Classification according to Regulation (EC) No 1272/2008**

Org. Perox. D	H242	Heating may cause a fire.
Eye Irrit. 2	H319	Causes serious eye irritation.
Skin Sens. 1	H317	May cause an allergic skin reaction.
Repr. 1A	H360D	May damage the unborn child.
Aquatic Acute 1	H400	Very toxic to aquatic life.
Aquatic Chronic 1	H410	Very toxic to aquatic life with long lasting effects.

2.2 Label elements:**Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

Hazard pictograms

GHS02 GHS07 GHS08 GHS09

Signal word Danger**Hazard-determining components of labelling:**Dicyclohexyl phthalate
Dibenzoyl peroxide

Safety data sheet
according to 1907/2006/EC, Article 31

Printing Date: 09.01.2020

Version Number: 1.0

Revision Date: 09.01.2020

Trade name: RIW FLEXISEAL 500 POWDER INITIATOR

(Contd. of page 1)

Hazard statements

H242 Heating may cause a fire.
 H319 Causes serious eye irritation.
 H317 May cause an allergic skin reaction.
 H360D May damage the unborn child.
 H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
 P273 Avoid release to the environment.
 P302+P352 IF ON SKIN: Wash with plenty of water.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P410 Protect from sunlight.

2.3 Other hazards:**Results of PBT and vPvB assessment:**

PBT: Not applicable.
vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Chemical characterization: Mixture:**Description:**

Mixture of substances listed below with non-hazardous additions.
 For further information, please refer to the product technical data sheet.

Dangerous components:

CAS: 94-36-0 EINECS: 202-327-6 Index number: 617-008-00-0 Reg.nr.: 01-2119511472-50-XXXX	Dibenzoyl peroxide	Org. Perox. B, H241 Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Eye Irrit. 2, H319; Skin Sens. 1, H317	30-<50%
CAS: 84-61-7 EINECS: 201-545-9 Index number: 607-719-00-4 Reg.nr.: 01-2119978223-34-XXXX	Dicyclohexyl phthalate	Repr. 1A, H360D Skin Sens. 1, H317	30-<50%

SVHC

84-61-7 | Dicyclohexyl phthalate

SECTION 4: First aid measures

4.1 Description of first aid measures:

General information: Get medical advice/attention if you feel unwell.

After inhalation: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

After skin contact: Wash with plenty of soap and water.

After eye contact: Rinse cautiously with water for several minutes.

After swallowing:

Rinse mouth.

Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed:

May cause sensitisation by skin contact.

Irritating to eyes.

(Contd. on page 3)

GB

Trade name: *RIW FLEXISEAL 500 POWDER INITIATOR*

(Contd. of page 2)

4.3 Indication of any immediate medical attention and special treatment needed:

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media:

Suitable extinguishing agents: CO₂, powder or water spray. Fight larger fires with water spray.

5.2 Special hazards arising from the substance or mixture: No further relevant information available.

5.3 Advice for firefighters:

Protective equipment: Wear self-contained respiratory protective device.

Additional information: Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

Ensure adequate ventilation.

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system.

6.3 Methods and material for containment and cleaning up:

Send for recovery or disposal in suitable receptacles.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling:

Do not eat, drink or smoke when using this product.

Store in a well-ventilated place. Keep container tightly closed.

Keep only in original packaging.

Use only outdoors or in a well-ventilated area.

Information about fire - and explosion protection:

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

7.2 Conditions for safe storage, including any incompatibilities:

STORAGE

Information about storage in one common storage facility: Keep respiratory protective device available.

Further information about storage conditions:

Keep container tightly sealed.

Store in a dry place.

Keep cool.

7.3 Specific end use(s): No further relevant information available.

GB

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing Date: 09.01.2020

Version Number: 1.0

Revision Date: 09.01.2020

Trade name: RIW FLEXISEAL 500 POWDER INITIATOR

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

Additional information about design of technical facilities: No further data; see item 7.

8.1 Control parameters:

Ingredients with limit values that require monitoring at the workplace:

94-36-0 Dibenzoyl peroxide

WEL | Long-term value: 5 mg/m³

84-61-7 Dicyclohexyl phthalate

WEL | Long-term value: 5 mg/m³

Additional information: Based on the lists valid at the date of SDS creation.

8.2 Exposure controls:

PERSONAL PROTECTIVE EQUIPMENT

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Respiratory protection:

Control exposure to ingredients with workplace control parameters if mentioned above. If no ingredients are listed, respiratory protection is generally not required.

If exposure limits are listed and may be exceeded, use approved respiratory protective equipment and filter type appropriate for the listed ingredients. (NIOSH, CEN, etc.).
EN 143.

Protection of hands:

Protective gloves.
EN 374.

Material of gloves: Rubber gloves.

Penetration time of glove material:

The exact breakthrough time has to be determined by the manufacturer of the protective gloves and has to be observed.

Eye protection:

EN 166.

Tightly sealed goggles.

Body protection:

Use personal protective equipment as required.

Take off contaminated clothing.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties:

GENERAL INFORMATION

Appearance:

Form: Powder.
Colour: According to product specification.
Odour: Characteristic.
Odour threshold: Not determined.

pH-value (~): Not applicable.

Change in conditions:-

Melting point/freezing point: Undetermined.
Initial boiling point and boiling range: Not determined.
Flash point: Not applicable.

Flammability (solid, gas): May cause fire.

Ignition temperature: Not determined.

(Contd. on page 5)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing Date: 09.01.2020

Version Number: 1.0

Revision Date: 09.01.2020

Trade name: RIW FLEXISEAL 500 POWDER INITIATOR

(Contd. of page 4)

Decomposition temperature:	Not determined.
Auto-ignition temperature:	Not determined.
Explosive properties:	Product does not present an explosion hazard.

EXPLOSION LIMITS	
Lower:	Not determined.
Upper:	Not determined.
VOC Content:	Not determined.

Vapour pressure:	Not applicable.
Density:	Not determined.
Relative density:	630 kg/m ³
Vapour density:	Not determined.

Solubility in/Miscibility with:-	
Water:	Insoluble.

Partition coefficient: n-octanol/water:	Not determined.
--	-----------------

VISCOSITY	
Dynamic:	Not applicable.
Kinematic:	Not applicable.
Molecular weight	Not applicable.

9.2 Other information:	No further relevant information available.
-------------------------------	--

SECTION 10: Stability and reactivity

10.1 Reactivity:

Stable under normal conditions.
No further relevant information available.

10.2 Chemical stability:

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions

No dangerous reactions known.
No further relevant information available.

10.4 Conditions to avoid: No further relevant information available.

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products: Carbon monoxide and carbon dioxide.

SECTION 11: Toxicological information

11.1 Information on toxicological effects:

ACUTE TOXICITY Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

84-61-7 Dicyclohexyl phthalate

Dermal	LD50	30,000 mg/kg (rat)
--------	------	--------------------

Primary irritant effect

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

May cause an allergic skin reaction.

Additional toxicological information:

84-61-7 Dicyclohexyl phthalate

NOEC/NOEL	mg/l (daphnia magna)
-----------	----------------------

(Contd. on page 6)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing Date: 09.01.2020

Version Number: 1.0

Revision Date: 09.01.2020

Trade name: RIW FLEXISEAL 500 POWDER INITIATOR

(Contd. of page 5)

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity
May damage the unborn child.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity:

AQUATIC TOXICITY

84-61-7 Dicyclohexyl phthalate

EC50, 48h	mg/l (daphnia magna)
Biodegradability	

12.2 Persistence and degradability: No further relevant information available.

12.3 Bioaccumulative potential: No further relevant information available.

12.4 Mobility in soil: No further relevant information available.

ADDITIONAL ECOLOGICAL INFORMATION

General notes:

Toxic for aquatic organisms.

Also poisonous for fish and plankton in water bodies.

Very toxic for aquatic organisms.

12.5 Results of PBT and vPvB assessment:

PBT: Not applicable.

vPvB: Not applicable.

12.6 Other adverse effects: No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods:

Recommendation:



Must not be disposed together with household garbage. Do not allow product to reach sewage system.

UNCLEANED PACKAGING

Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

14.1 UN-Number

ADR, IMDG, IATA

UN3106

14.2 UN proper shipping name

ADR

ORGANIC PEROXIDE TYPE D, SOLID (Dibenzoyl peroxide), ENVIRONMENTALLY HAZARDOUS

(Contd. on page 7)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing Date: 09.01.2020

Version Number: 1.0

Revision Date: 09.01.2020

Trade name: RIW FLEXISEAL 500 POWDER INITIATOR

(Contd. of page 6)

IMDG	ORGANIC PEROXIDE TYPE D, SOLID (Dibenzoyl peroxide), MARINE POLLUTANT
IATA	ORGANIC PEROXIDE TYPE D, SOLID (Dibenzoyl peroxide)

14.3 Transport hazard class(es)

ADR, IMDG



Class Label	5.2 Organic peroxides. 5.2
--------------------	-------------------------------

IATA



Class Label	5.2 Organic peroxides. 5.2
--------------------	-------------------------------

14.4 Packing group

ADR, IMDG, IATA II

14.5 Environmental hazards:

Marine pollutant:	Symbol (fish and tree)
Special marking (ADR):	Symbol (fish and tree)

14.6 Special precautions for user:

Danger code (Kemler):	Warning: Organic peroxides. 539
EMS Number:	F-J,S-R
Stowage Category	D
Stowage Code	SW1 Protected from sources of heat.
Segregation Code	SG35 Stow "separated from" SGG1-acids SG36 Stow "separated from" SGG18-alkalis.

14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:

Not Regulated

Transport/Additional information:

ADR	
Transport category	2
Tunnel restriction code	D

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:**

See Section 2 for hazard identification.

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category

P6b SELF-REACTIVE SUBSTANCES AND MIXTURES and ORGANIC PEROXIDES

E1 Hazardous to the Aquatic Environment

Qualifying quantity (tonnes) for the application of lower-tier requirements 50 t**Qualifying quantity (tonnes) for the application of upper-tier requirements** 200 t**15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

GB

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing Date: 09.01.2020

Version Number: 1.0

Revision Date: 09.01.2020

Trade name: RIW FLEXISEAL 500 POWDER INITIATOR

(Contd. of page 7)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases:

- H241 Heating may cause a fire or explosion.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H360D May damage the unborn child.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.

Department issuing SDS:

Product Stewardship Department
GCP Applied Technologies
580-581 Ipswich Road,
Slough, Berkshire.
SL1 4EQ

Tel: +44 (0)1753 490 000

Fax: +44 (0)1753 490 001

The first date of preparation: 09.01.2020**Number of revision times and the latest revision date:** 1.0 / 09.01.2020

GB